


beledi

LED
BatWing

B·A·R·O
PERFECT RETAIL LIGHTING



70 000 ...

LED linear system, passive cooling, reflector with double asymmetrical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, extruded aluminium sheath luminaire housing, anodized or powder-coated, driver unit 220-240 V, 50/60 Hz

- Anodized aluminium**
- ... 006 39W 2x20° 3,000 K
- ... 007 4,000 K
- ... 023 2x30° 3,000 K
- ... 024 4,000 K
- ... 001 48W 2x20° 3,000 K
- ... 008 4,000 K
- ... 025 2x30° 3,000 K
- ... 026 4,000 K



- Strato white**
- ... 009 39W 2x20° 3,000 K
- ... 010 4,000 K
- ... 027 2x30° 3,000 K
- ... 028 4,000 K
- ... 011 48W 2x20° 3,000 K
- ... 012 4,000 K
- ... 029 2x30° 3,000 K
- ... 030 4,000 K

| Lighting technology | 39 W | 48 W |
|---------------------|-------------------|-------------------|
| Design | linear | linear |
| Light colour | 3,000 . 4,000 K | 3,000 . 4,000 K |
| Utilised flux | 3,950 . 4,150 lm | 4,800 . 5,100 lm |
| System power | 39 W | 48 W |
| Reflector | BatWing | BatWing |
| Beam angle | 2 x 20° . 2 x 30° | 2 x 20° . 2 x 30° |
| Reflector colours | Silver | Silver |

| Luminaire | 5.0 kg |
|--------------------------------------|--|
| Weight | 5.0 kg |
| Protection rating . Protection class | IP 20 . I |
| Luminaire colours | <input checked="" type="checkbox"/> <input type="checkbox"/> |

- Including**
- Driver unit
 - Feed-through wiring set


- Accessories**
- Connector
 - Front plates, anodized aluminium
 - Suspension . Ceiling fixture



Note
Due to further developments in the field of LED technology, the system power may be reduced within the framework of product upgrades

beledi

LED WideWing




70 000 ...
LED linear system, passive cooling, grid with double asymmetrical light distribution pattern, 99.99% pure aluminium grid made of MIRO-SILVER®, extruded aluminium sheath luminaire housing, anodized or powder-coated, driver unit 220-240 V, 50/60 Hz

Anodized aluminium
... 055 39 W 2 x 25° 3,000 K
... 056 4,000 K
... 057 48 W 2 x 25° 3,000 K
... 058 4,000 K

Strato white
... 059 39 W 2 x 25° 3,000 K
... 060 4,000 K
... 061 48 W 2 x 25° 3,000 K
... 062 4,000 K

| Lighting technology | 39 W | 48 W |
|---------------------|------------------|------------------|
| Design | linear | linear |
| Light colour | 3,000 . 4,000 K | 3,000 . 4,000 K |
| Utilised flux | 3,875 . 4,050 lm | 4,700 . 5,000 lm |
| System power | 39 W | 48 W |
| Raster | WideWing | WideWing |
| Beam angle | 2 x 25° | 2 x 25° |
| Reflector colours | Silver | Silver |

| Luminaire | 5.0 kg |
|--------------------------------------|--|
| Weight | 5.0 kg |
| Protection rating . Protection class | IP 20 . I |
| Luminaire colours | <input checked="" type="checkbox"/> <input type="checkbox"/> |



| LED 39 W | 3,000 K | 4,000 K |
|----------|--------------|---------------|
| 1 | 1.50 . 2.10 | 1,535 . 1,610 |
| 2 | 3.00 . 4.20 | 385 . 405 |
| 3 | 4.50 . 6.30 | 170 . 180 |
| 4 | 6.00 . 8.40 | 95 . 100 |
| 5 | 7.50 . 10.60 | 60 . 65 |
| h (m) | Ø (m) | E (lx) |

| LED 48 W | 3,000 K | 4,000 K |
|----------|--------------|---------------|
| 1 | 1.50 . 2.10 | 1,865 . 1,980 |
| 2 | 3.00 . 4.20 | 465 . 495 |
| 3 | 4.50 . 6.30 | 210 . 220 |
| 4 | 6.00 . 8.40 | 115 . 125 |
| 5 | 7.50 . 10.60 | 75 . 80 |
| h (m) | Ø (m) | E (lx) |

Including
Driver unit
Feed-through wiring set


Accessories
Connector
Front plates, anodized aluminium
Suspension . Ceiling fixture

Note
Due to further developments in the field of LED technology, the system power may be reduced within the framework of product upgrades

beledi

LED
WideBeam

B.A.RO
PERFECT RETAIL LIGHTING




70 000 ...
LED linear system, passive cooling, grid with broad light distribution pattern, UGR 19, 99.99% pure aluminium grid made of MIRO-SILVER®, extruded aluminium sheath luminaire housing, anodized or powder-coated, driver unit 220-240 V, 50/60 Hz

Anodized aluminium
... 047 39 W 3,000 K
... 048 4,000 K
... 049 48 W 3,000 K
... 050 4,000 K

Strato white
... 051 39 W 3,000 K
... 052 4,000 K
... 053 48 W 3,000 K
... 054 4,000 K

| Lighting technology | 39 W | 48 W |
|---------------------|------------------|------------------|
| Design | linear | linear |
| Light colour | 3,000 . 4,000 K | 3,000 . 4,000 K |
| Utilised flux | 3,775 . 3,975 lm | 4,600 . 4,875 lm |
| System power | 39 W | 48 W |
| Raster | WideBeam | WideBeam |
| Beam angle | 80° x 100° | 80° x 100° |
| Reflector colours | Silver | Silver |

Luminaire
Weight 5.0 kg
Protection rating . Protection class IP 20 . I
Luminaire colours



| LED 39 W | 3,000 K | 4,000 K |
|----------|--------------|---------------|
| 1 | 1.65 . 2.25 | 1,875 . 1,985 |
| 2 | 3.30 . 4.50 | 470 . 495 |
| 3 | 4.95 . 6.75 | 210 . 220 |
| 4 | 6.60 . 9.00 | 120 . 125 |
| 5 | 8.25 . 11.25 | 75 . 80 |
| h (m) | Ø (m) | E (lx) |

Including
Driver unit
Feed-through wiring set

| LED 48 W | 3,000 K | 4,000 K |
|----------|--------------|---------------|
| 1 | 1.65 . 2.25 | 2,290 . 2,480 |
| 2 | 3.30 . 4.50 | 570 . 620 |
| 3 | 4.95 . 6.75 | 255 . 275 |
| 4 | 6.60 . 9.00 | 145 . 155 |
| 5 | 8.25 . 11.25 | 90 . 100 |
| h (m) | Ø (m) | E (lx) |

Accessories
Connector
Front plates, anodized aluminium
Suspension . Ceiling fixture

Note
Due to further developments in the field of LED technology, the system power may be reduced within the framework of product upgrades